

Silicone boots and grommets for applications in heating equipment

High temperature edge grommets and sleeved grommets

Flammability: UL 94-V0

Hardness: 60 Shore A

Color: black. Other colors available (MOQ apply)

For temperatures higher than 200°C, see ceramic grommets (Ceramic connection blocks Catalogue N°10)



9BBCE100000025A	9BBCE100000025A	9BBJO1000CAB004A	9BBJO1000CAB002A
Edge grommet for hole dia. 12.5 to 13 mm, wall thickness 1mm, cable diameter 9mm max.	Edge grommet for hole dia. 12.5 to 13 mm, wall thickness 1mm, cable diameter 11mm max.	Edge grommet for hole dia. 26 to 27 mm, wall thickness 2mm, cable diameter 24mm max.	Edge grommet for hole dia. 50 to 51 mm, wall thickness 2mm, cable diameter 47 mm max.
9BBJO1000CAP002A	9BBJO1000004039A	9BBJO1000004038A	9BBJO1000004040A
Edge grommet for hole dia. 52 to 53 mm, wall thickness 2.5mm, cable diameter 28 mm max. Double ingress protection lips on cable.	Edge grommet for hole dia. 15mm mm, wall thickness 2 mm, cable diameter 9 to 10 mm max.	Edge grommet for hole dia. 15mm mm, wall thickness 2 mm, cable diameter 11 to 12 mm max.	Edge grommet for hole dia. 15 mm, wall thickness 2 mm, 2 wires diameter 3 mm max.
9BBJO1000004041A	9BBJO1000004042A	9BBJO1000004043A	9BBJO1000AFS002A
Edge grommet for hole dia. 15 mm, wall thickness 2 mm, 3 wires diameter 3 mm max.	Edge grommet for hole dia. 15 mm, wall thickness 2 mm, 4 wires diameter 3 mm max.	Edge grommet for hole dia. 15 mm, wall thickness 2 mm, 6 wires diameter 3 mm max.	Sleeve grommet for square hole 12x12mm, wall thickness 2.5mm, dia. 5 to 8 mm cable.

Because of permanent improvement of our products, drawings, descriptions, features used on these data sheets are for guidance only and can be modified without prior advice

